



Product Highlights:

- Designed for use with CFexpress™ Type A and SD™ UHS-II memory cards
- High-speed USB 10Gbps (USB 3.2 Gen 2) transfer speeds with USB Type-C®
- CFexpress™ Type A memory card transfer speed up to 900MB/s¹
- UHS-II SD™ memory card transfer speed up to 312MB/s¹
- Includes 2-in-1 USB Type-C and USB Type-A cable
- Compact and portable design for photographers and videographers on the go
- Two-year limited warranty



Versatile card reader for more efficient workflows

Optimized for the new Lexar® CFexpress™ Type A memory cards, the CFexpress™ Type A/SD™ Card reader provides high-speed USB 10Gbps (USB 3.2 Gen 2) transfer speeds, allowing content creators to establish an efficient workflow when transferring high-resolution photos and video content.

Save time with dual-slot design. Lexar® Professional CFexpress™ Type A/SD™ USB 3.2 Gen 2 Reader supports simultaneous high-speed transfers of CFexpress™ Type A and SD™ memory cards at the same time, accelerating your workflow and saving you time.

Streamline your workflow with 10Gb/s speeds. With USB 3.2 Gen 2 support, Lexar® Professional CFexpress™ Type A/SD™ USB 3.2 Gen 2 Reader supports the high-speed 10Gbps transfers with USB Type-C®, making it easy to transfer large files and 8K videos in seconds.

Compact and durable design. The Lexar® Professional CFexpress™ Type A/SD™ USB 3.2 Gen 2 Reader features a lightweight design that allows you to fit the reader into your pocket or bag with ease, making it ideal for transferring your data on the go. And with the metal surface, which is resistant to wear and tear, the reader is as durable as it is stylish.

Rigorously tested. All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 25 years, Lexar has been a trusted leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

¹Designed for CFexpress™ Type A memory cards, support for all CFexpress™ Type A memory cards are not guaranteed. Results may vary based on system configuration and card speed.

Warning: Compatible with CFexpress™ Type A memory cards and SD™ memory cards only, as clearly indicated by the framed USB label on the card. Use of incompatible memory cards will result in data loss. For more information on memory cards, please consult the card manufacturer.

Lexar is not liable for any loss of data or images.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

www.lexar.com

©2022 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Lexar Retail Sku	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LRW530U-RNBNG	Global	843367128136	10843367128133	10

Specifications

Interface	Type-C
Speed	CFexpress™ Type A memory card transfer speed up to 900MB/s ¹ , UHS-II SD™ memory card transfer speed up to 312MB/s ¹
Indicator status	Power on: White Insert memory card: White flashing Data transfer: White flashing
Supported card formats	CFexpress™ Type A memory card SD™,SDHC™, SDXC™ UHS-I and UHS-II memory card
System Supported	Mac® OS 10.8+, Windows® 11/10/8/7/Vista/XP, USB 2.0+ port
Operating Temperature	0° to 40° C (32°F to 104°F)
Storage Temperature	-20°C to 85°C (-4°F to 185°F)
Shock	1500G, duration 0.5ms, Half Sine Wave
Vibration	0~2000Hz, 1.5mm, 20G, 1 Oct/min, 30min/axis(X,Y,Z)
Dimension (W x L x H)	98 x 59.98 x 19.08 mm / 3.90" x 2.40" x 0.75"
Weight	77g / 0.17lbs
Warranty	Two-year limited warranty

www.lexar.com

©2022 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.